TWISTED ROPE



Color Selection Black, White, Blue, Red, Green, Yellow
Packaging Selections Packaging: Hank, Clamshell, Coil, Reel
Product Number Twisted Rope

GALLERY IMAGES



Address in Charles 102, Unit.2, B

n: 9F-3, No. 202, Sec. 3, Da-Tong Road, Hsi-Chih District, New Taipei City, Taiwan 22103
102, Unit.2, Build. 24, No.417, Xing Yang Road, Cheng Yang District, Qingdao, China, 266109
Tel: +886-286471778 Email: panjack.co@msa.hinet.net



Address in Taiwan: 9F-3, No. 202, Sec. 3, Da-Tong Road, Hsi-Chih District, New Taipei City, Taiwan 22103

Address in China: Room 102, Unit.2, Build. 24, No.417, Xing Yang Road, Cheng Yang District, Qingdao, China, 266109

Tel: +886-286471778 Email: panjack.co@msa.hinet.net

ADDITIONAL INFORMATION

SPECIFICATION

Material: PP Multifilament (MFP) / Polyester / Nylon / PP Monofilament / PE

* Custom Branded Available

PP MULTIFILAMENT (MFP) TWISTED ROPE

- It Has Low Abrasion Resistance and is Affected by Sunlight

POLYESTER MULTIFILAMENT TWISTED ROPE

It Is an Excellent in Resistance to Abrasion & Sunlight and Easy to Splice and Can for Mooring,
 Anchor, Fender Lines

PP MONOFILAMENT TWISTED ROPE

- It Is Strong, Lightweight, Spliceable and Used Extensively for Most rope Requirements

NYLON MULTIFILAMENT TWISTED ROPE

- Strong, Durable, Flexible and Shock Absorbent. .
 - For Docking, Anchoring or Pulling.

PE TWISTED ROPE

- It Is Floatable, and Highly Resistant to Most Chemicals, Spliceable, Low Stretch

Diameter	Length	Packaging
3/16″	30′, 50′, 100′ (1200′, 2125′)	Hank (Reel)
1/4″	50′, 100′ (900′, 1200′)	Hank (Reel)
3/8″	50′, 100′ (300′, 600′)	Hank (Reel)
5/16″	50′, 100′ (600′, 900′)	Hank (Reel)
1/2″	50′, 100′ (150′, 400′)	Hank (Reel)
5/8″	50′, 100′ (300′)	Hank (Reel)
3/4″	50, 100′ (200′)	Hank (Reel)

PP MULTIFILAMENT (MFP) TWISTED ROPE

- It Has Low Abrasion Resistance and is Affected by Sunlight

POLYESTER MULTIFILAMENT TWISTED ROPE

It Is an Excellent in Resistance to Abrasion & Sunlight and Easy to Splice and Can for Mooring,
 Anchor, Fender Lines

PP MONOFILAMENT TWISTED ROPE

- It Is Strong, Lightweight, Spliceable and Used Extensively for Most rope Requirements

NYLON MULTIFILAMENT TWISTED ROPE

– Strong, Durable, Flexible and Shock Absorbent. Spliceable Address in Taiwan: 9F-3, No. 202_Sec. 3, Da-Tong Road, Hsi-Chih District, New Taipei City, Taiwan 22103 – For Docking, Anchoring or Pulling.

Address in China: Room 102, Unit.2, Build. 24, No. 447, King Yang District, Qingdao, China, 266109

- It is Floatable, a Ted: HR\$P61→8Re3137871€ntoil Mrostia Chengiocats hisetice able, Low Stretch

Diameter (mm)	Length (M)	Packaging
4	Page: 3	Coil
6, 8, 10, 12, 14, 16	100, 220	Coil

18, 20, 24, 26, 28, 30, 32, 36	100	Coil
--------------------------------	-----	------

Address in Taiwan: 9F-3, No. 202, Sec. 3, Da-Tong Road, Hsi-Chih District, New Taipei City, Taiwan 22103

Address in China: Room 102, Unit.2, Build. 24, No.417, Xing Yang Road, Cheng Yang District, Qingdao, China, 266109

Tel: +886-286471778 Email: panjack.co@msa.hinet.net